



MATEBOX

For the new X-ESS G4, we get rid of the complicated wiring work by laying all the wires in the Matebox. All you need to do is just install one module on the top of another, and connect all the cables which are already well-sorted in the Matebox in different ports.

PV	
Max. input voltage [Vdc]	600
Max. short circuit current (A/B) [A]	18/18
BATTERY	
Battery voltage range [V]	80-480
Max. charge/discharge current [A]	30
ON-GRID(Inverter)	
Rated voltage [Vac], frequency [Hz]	220/230/240, 50/60
Max. on-grid current [A]	32.6
OFF-GRID(Inverter)	
Rated voltage [Vac], frequency [Hz]	230, 50/60
Rated current [A]	32.6
GRID(Utility)	
Rated grid voltage [Vac], frequency [Hz]	220/230/240, 50/60
Max. input current [A]	60
LOAD	
Rated voltage [Vac], frequency [Hz]	220/230/240, 50/60
Max. current [A]	60
ENVIRONMENT LIMIT	
Degree of protection	IP54
Protection class	Class I
Operating temperature range [°C]	-25~+60°C (Derating above +45°C)
Storage temperature [°C]	-40~+70°C
Relative humidity [%]	0~100 (condensing)
Altitude[m]	<3000
Overvoltage category	III(AC), II(DC)
OTHER	
Cooling concept	Nature cooling
DIMENSION AND WEIGHT	
Dimensions [mm]	482x437x185
Net weight [kg]	10.5

X1-MATEBOX



X3-MATEBOX BASIC



X3-MATEBOX ADVANCED



PV	
Max. input voltage[Vdc]	1000
Max. short circuit current (A/B)[A]	30/18
BATTERY	
Battery voltage range[V]	180~650
Max.charge/discharge current[A]	30
ON-GRID(Inverter)	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. Grid(INV) input/output current[A]	32/32
OFF-GRID(Inverter)	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. current[A]	24.1
GRID(Utility)	
Rated grid voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. input/output current[A]	32/32
LOAD	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. current[A]	24.1
ENVIRONMENT LIMIT	
Degree of protection	IP54
Protection class	Class I
Operating temperature range[°C]	-25~+60°C (Derating above +45°C)
Storage temperature[°C]	-40~+70°C
Relative humidity[%]	0~100
Altitude[m]	<3000
Overvoltage category	III(AC), II(DC)
OTHER	
Cooling concept	Nature cooling
DIMENSION AND WEIGHT	
Dimensions[mm]	533x397x204
Net weight[kg]	7.5

PV	
Max. input voltage[Vdc]	1000
Max. short circuit current (A/B)[A]	30/18
BATTERY	
Battery voltage range[V]	180~650
Max. charge/discharge current[A]	30
ON-GRID(Inverter)	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. Grid(INV) input/output current[A]	24.1/24.1
OFF-GRID(Inverter)	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. current[A]	24.1
GRID(Utility)	
Rated grid voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. input/output current[A]	63/24.1
LOAD	
Rated voltage[Vac], frequency[Hz]	380/400/415, 50/60
Max. current[A]	63
ENVIRONMENT LIMIT	
Degree of protection	IP54
Protection class	Class I
Operating temperature range[°C]	-25~+60°C (Derating above +45°C)
Storage temperature[°C]	-40~+70°C
Relative humidity[%]	0~100
Altitude[m]	<3000
Overvoltage category	III(AC), II(DC)
OTHER	
Cooling concept	Nature cooling
DIMENSION AND WEIGHT	
Dimensions[mm]	551x512x204
Net weight[kg]	14.5